CLAIMS

What is claimed is:

1. A method for providing a system of free-space electromagnetic pathways to facil	шиац
--	------

- 2 wireless networking of computing devices, each computing device having a line-of-sight
- 3 transceiver, the method comprising:
- 4 attaching a reflector to a surface of an object to create a reflective surface such that a
- 5 beamed communication sent from a line-of-sight transceiver at a first location is reflected in a
- 6 direction towards a second line-of-sight transceiver at a second location.
 - 2. The method of claim 1 further comprising:

providing a first location within the system adjacent the reflector for a user of a first computing device; and

providing a second location within the system adjacent the reflector for a user of a second computing device.

3. The method of claim 1, wherein the reflector is a first reflector, further comprising:

attaching a second reflector to a surface of a second object to create a reflective

- surface such that the beamed communication received by the second transceiver and
- 4 subsequently re-transmitted is reflected in a direction towards a third line-of-sight transceiver
- 5 at a third location.

- 1 4. The method of claim 3 further comprising:
- 2 providing a third location within the system adjacent the second reflector for a user of
- a computing device.
- 1 5. The method of claim 1 wherein the step of attaching further comprises

- 2 attaching the reflector so that it has a curvature that disperses the beamed
- 3 communication such that the second line-of-sight transceiver and a third the line-of-sight
- 4 transceiver can receive the beamed communication.
- 1 6. The method of claim 5 further comprising transmitting the beamed communication using
- 2 multicast packets.

4

- 1 7. The method of claim 5 further comprising transmitting the beamed communication in
- 2 accordance to a multi-hop protocol.
- 1 8. The method of claim 1 further comprising providing the reflector that conforms to a
- 2 curvature of the surface of the object.
 - 9. The method of claim 1 further comprising providing the reflector shaped to produce a predefined curvature on the surface of the object.
 - 10. The method of claim 9 wherein the step of providing the reflector further comprises providing the reflector with the predefined curvature being arcuate.
 - 11. The method of claim 1 further comprising transmitting the beamed communication using light with an infrared wavelength.
 - 12. The method of claim 1 further comprising using the computing device that is a personal
- 2 digital assistant.
- 1 13. The method of claim 1 wherein the attaching step further comprises attaching the
- 2 reflector to a chair.
- 1 14. A system of free-space electromagnetic pathways for facilitating wireless networking of a
- 2 plurality computing devices, each computing device having a transceiver for beamed line-of-
- 3 sight, electromagnetic communication, the communication channel comprising:
- a first location at which one of the plurality of computing devices is used;

- a second location at which another of the plurality of computing devices is used; and
- a reflective surface purposely disposed adjacent the first and second locations such 6
- that a beamed communication transmitted from the first location is reflected in a direction 7
- 8 towards the second location.
- 1 15. The system of claim 14 further comprising:
- 2 a third location at which another of the plurality of computing devices is used; and
- a reflective surface purposely disposed adjacent the second and third locations such 3
- that the beamed communication received at and re-transmitted from the second location is 4
- 5 reflected in a direction towards the third location.
 - 16. The system of claim 15 wherein the beamed communication includes a multicast packet.
 - 17. The system of claim 15 wherein the beamed communication traverses the network in accordance to a multi-hop protocol.
 - 18. The system of claim 14 wherein the reflective surface has a curvature that disperses the beamed communication such that the beamed communication transmitted from the first location is received at the second location and the third location.
 - 19. The system of claim 14 wherein the reflective surface conforms to a curvature of a surface of an object to which the reflective surface is attached.
- 20. The system of claim 14 wherein the reflective surface is shaped to produce a predefined 1
- 2 curvature on a surface of an object to which the reflective surface is attached.
- 21. The system of claim 20 wherein the predefined curvature of the reflector is arcuate. 1
- 1 22. The system of claim 14 wherein the object is a chair.
- 23. The system of claim 14 wherein the beamed communication uses light with an infrared 1
- wavelength. 2

- 1 24. The system of claim 14 wherein the beamed communication uses microwaves.
- 1 25. The system of claim 14 wherein the computing devices are personal digital assistants.
- 1 26. A wireless network of line-of-sight computing devices, the network comprising:
- a first computing device having a line-of-sight transceiver;
- a second computing device having a line-of-sight transceiver; and
- 4 a reflector attached to a surface of an object adjacent the first and second computing
- 5 devices such that a beamed communication sent from the transceiver of the first computing
- 6 device is reflected in a direction towards the transceiver of the second computing device.
- 1 27. The wireless network of claim 26 further comprising:
 - a third computing device having a line-of-sight transceiver; and
- a second reflector attached to a surface of a second object adjacent the second
 - computing device such that the beamed communication received by the second computing
 - device and subsequently re-transmitted by the second computing device is reflected in a
 - direction towards the transceiver of the third computing device.
 - 28. The wireless network of claim 27 wherein the beamed communication includes a
 - multicast packet.

- 29. The wireless network of claim 27 wherein the beamed communication traverses the
- 2 wireless network in accordance to a multi-hop protocol.
- 1 30. The wireless network of claim 26 wherein the reflector has a curvature that disperses the
- 2 beamed communication such that the transceiver of the second computing device and the
- 3 transceiver of a third computing device can receive the beamed communication.
- 1 31. The wireless network of claim 26 wherein the reflector conforms to a curvature of the
- 2 surface of the object.

- 1 32. The wireless network of claim 26 wherein the reflector is shaped to produce a predefined
- 2 curvature on the surface of the object.
- 1 33. The wireless network of claim 32 wherein the predefined curvature of the reflector is
- 2 arcuate.
- 1 34. The wireless network of claim 26 wherein the beamed communication uses light with an
- 2 infrared wavelength.
- 1 35. The wireless network of claim 26 wherein the computing devices are personal digital
- 2 assistants.
- 1 36. The wireless network of claim 26 wherein the object is a chair.